

# **AGENDA ITEM 5**


APPENDIX 1b

2020/0077/MSC

**PLANS** 








# MANHOLE SCHEDULE


# Sheet 1 of 1


Manhole Number		Cover Level		Pipe				Manhole Size	Types	
(	Coordinates	Depth To Soffit	Connections	Code		Inverts	Diams Inv-soff	3.20	Manhole	Cover
	S1	241.675								
E.	278225.001	1.375						1200	В	Unspec
N.	802071.448		Ŏ	0	1.000	240.075	225			
	S2	241.391								
E.	278243.378	1.375						1200	В	Unspec
N.	802041.448		Ŏ	0	2.000	239.791	225			
	S3	241.526		1 2	2.000 1.000	239.515 239.515	225 225			
E.	278234.949	1.786	2 1					1350	В	Unspec
N.	802055.176		ŏ	0	1.001	239.365	375			
	S4	240.500	1	1	1.001	239.150	375			
E.	278181.595	0.975						1350	В	Unspec
N.	802023.747		0	0	1.002	239.150	375			
	S5	240.500	1	1	1.002	239.000	375			
E.	278176.124	1.125						1350	Control Chamber	Unspec
N.	802000.977		Ŏ	0	1.003	239.000	375			

Pipe	Diameter	Gradient	Pipe	Upstream Manhole			Downstream Manhole		
Code	(mm)	(1:)	Length	Number Invert		Cover	Number	Invert	Cover
1.000	225	34	19.072	S1	240.08	241.68	S3	239.52	241.50
1.001	375	288	61.923	S3	239.37	241.53	S4	239.15	240.50
1.002	375	156	23.418	S4	239.15	240.50	S5	239.00	240.50
1.003	375	11	15.070	S5	239.00	240.50	S_	237.61	239.00
2.000	225	58	16.109	S2	239.79	241.39	S3	239.52	241.53

P01	23.01.20	For client	issue	LG				
Revision	Date	Descript	tion	Initials				
EnvironmentalConsultants  111 McDonald Road, EDINBURGH, EH7 4NW 0131 550 6500   mail@ironsidefarrar.com EDINBURGH   BELLSHILL   MANCHESTER								
Farm Relocation Balavil Client								
Balavil Estate								
Tist-								
Title Prop	osed Di	ainage						
Prop	osed Di itudinal	ainage Sections						
Prop Long	itudinal	•						
Prop Long	itudinal	Sections on 2-M and 2-N  Bar Scale	12.5	25m				
Prope Long PPP	itudinal Conditi Scale 1:5 Scale	Sections on 2-M and 2-N 00 Bar Scale 0 1:500 aper Size Quality Assuranc ISO 9001:2015		25m				
Proportions PPP  N. Point  Date 23.0′  Drawn By  LG	itudinal Conditi Scale 1:5 Scale 1.20	Sections on 2-M and 2-N  Bar Scale 0  1:500  aper Size 1  Quality Assuranc ISO 9001:2015 SGS UKAS Cer Copyright Acknow Ordnance Surve	e tificate GB02/54539					
Proportions Propor	itudinal Conditi Scale 1:5 Scale	Sections on 2-M and 2-N  Bar Scale 0  1:500  aper Size 1  Quality Assuranc ISO 9001:2015 SGS UKAS Cer Copyright Acknow Ordnance Surve	e tificate GB02/54539 Wedgement ey © Crown Copyright 2019					
Proportions Propor	itudinal Conditi 1:5 Scale 1.20	Sections on 2-M and 2-N  Bar Scale 0  1:500  aper Size 1  Quality Assuranc ISO 9001:2015 SGS UKAS Cer Copyright Acknow Ordnance Surve All rights reserv	e tificate GB02/54539 Wedgement ey © Crown Copyright 2019					








DETAIL 3
FILTER TRENCH CATCHPIT DETAIL
SCALE (1:20)

75mm BLINDING CONCRETE



2 No. 50mmØ Perforated Pipes with filter material surround (single sized granular material, 14mm no Limestone)

Output

DETAIL 6

DETAIL 6

MAIN "LOW FLOW" CHANNEL

SCALE 1:10

#### Notes:

- Refer to "Sewers for Scotland, 4th Edition" for typical details of manholes with depths from cover level to soffit of pipe not exceeding 6m. No significant departure from these shall be made without the approval of Highland Council. Types D&F need the agreement of Scottish Water. Manholes should be designed and constructed in accordance with BS EN 752-3.
- 2. Manhole diameter to be as follows: 1200mmØ (Pipe Ø up to 375mm.)
  - 1500mmØ (Pipe Ø > 375mm up to 700mm.)
  - 1800mmØ (Pipe  $\varnothing > 750$ mm up to 900mm.)
- 3. Manhole construction to be in accordance with "Sewers for Scotland, Fourth Edition", (SFS4).
- 4. Manhole covers and frames to be in accordance with SFS4 sub-section 5.2.30.
- 5. Rocker pipes shall be provided at entry to and exits from manholes. Their length shall be as shown in the Table in sub-section 5.6.6 of SFS4.
- 6. Where step rungs and ladders are to be used top-step rungs are to be located not less than 500mm and not greater than 700mm from the finished manhole cover level with a minimum of two courses of brickwork.
- 7. Chambers more than 450mm in depth have to have one or more step rungs or toe holes and 25mm diameter solid bar handrail to be provided to the benching.
- 8. Where no step rungs are to be used, there shall be between two and four courses of brickwork under cover.
- 9. Refer to SFS4 sub-section 2.20.7 for minimum clear access opening sizes and requirements for fittings.
- 10. Pipes of different diameters entering manholes shall be installed with soffits at the same level.
- 11. Clause numbers to the Specification for Highway Works (S.H.W.)
- 12. Pipe materials shall be in accordance with part 4 Sewers for Scotland 4th Edition.
- 13. The use of perfect manhole or similar precast base units shall be precluded without the express consent of the engineer.



# Mound Filter System

Calculations to BRE Digest No. 478, Mound Filter Systems for the Treatment of Domestic Wastewater

Vp from percolations text results = 186.9

## Minimum Basal Area

 $At = P \times Vp \times 0.25$ 

<i>P</i> =	Population Equivalent	6
Vp =	Percolation value of the native soil (s/mm)	186.9
At =	Area	280.3 m <sup>2</sup>

### Minimum Distribution Layer Area

 $Ad = P \times Vf \times 0.25$ 

<i>P</i> =	Population Equivalent	6
<b>∨</b> f =	Percolation value of filter material (s/mm)	35
Ad =	Distribution layer area (m²)	52.5 m²
		·

## Length of Pipework within Distribution Layer

Ad =		52.5
Pipes =	Adopt 5 pipes	5
Length =	Length of each pipe	10.5 m

Assuming 6.0m distribution layer width.


Therefore Width between pipes 1.2 m

Therefore distribution layer area =  $10.5 \text{ m} \times 6.0 \text{m} = 63.00 \text{ m}^2$ 

### Resultant Mound Dimension

The resultant dimension meet the critical dimension for distribution layers bed as per BRE 478 - Fig 14 and Figure.

_		
A =	Distribution layer width	6.00 m
B =	Distribution layer length	10.50 m
C =	Downslope taper	9.61 m
D =	Depth of filter material at the upslope edge	0.33 m
E =	Depth of filter material at the downslope edge	1.14 m
F =	Depth of gravel in the distribution layer	0.20 m
G =	Depth of the cover at the upslope and downslope	0.30 m
H =	Depth of cover at the centre of the distribution layer	1.40 m
J =	Upslope taper	1.50 m
K =	Sideslope taper	5.75 m
L =	Total length of mound [B+2K]	21.90 m
<b>VV</b> =	Total Width of the Mound [A+C+J]	17.11 m
X =	Total height of mound H+J+[(D+E)/2]	2.34 m
Ad =	Distribution Layer Area	63.0 m²
At =	Mound Basal Area (L X w)	371.5 m <sup>2</sup>
X =	Height	2.3 m <sup>2</sup>





DATOM 233	0.000									
Chainage	0.000	2.000	4.000	6.000	8.000	10.000	12.000	14.000	16.000	18.000
Existing Ground Level	239.316	239.022	238.749	238.499	238.226	237.955	237.680	237.410	237.131	236.787 236.741
Proposed Level	241.051	241.034	241.018	241.002	240.797	239.987	239.178	238.398	237.622	236.845 236.741


Mound Filter Cross Section A-A'

Scale H 1:50 V 1:50 1. The area required for the mound shall be fenced to avoid traffic and constructions. This will prevent disturbance, scalping or compaction of the mound.

2. The septic and infiltration system shall be inspected annually.







SGS UKAS Certificate GB02/54539 Copyright Acknowledgement
Ordnance Survey © Crown Copyright 2019
All rights reserved. Licence No. AL100017966 FOR APPROVAL P02

Project No Drawing No 50499-404

Drawn By

